

200 270

PRO-GLEAM UHS PRO-GLEAM UHS

200, 270 Burnisher Specifications



| | 200-UHS | 270-UHS |
|--|--|--|
| BODY CONSTRUCTION / DIMENSIONS | | |
| | 20" (51 cm) Walk Behind | 27" (69 cm) Walk Behind |
| Frame (Powder Coated Steel): | 10-ga. (1/8") (.3175 cm) | 10-ga. (1/8") (.3175 cm) |
| Rear Axle Capacity | 1,200 lbs. (544 kg) | 1,200 lbs. (544 kg) |
| Rear Wheels (non-marking) | (2) 8" x 2" (20 cm x 5 cm) | (2) 8" x 2" (20 cm x 5 cm) |
| Front Wheel (non-marking) | (2) 4" x 2" (10 cm x 5 cm) | (2) 4" x 2" (10 cm x 5 cm) |
| Dimensions (L x W x H): | 44" x 24" x 40" (112 cm x 61 cm x 102 cm) | 52" x 24" x 40" (132 cm x 61 cm x 102 cm) |
| Weight (w/batteries) | 602 lbs. (273 kg) | 652 lbs. (296 kg) |
| Weight (w/out batteries) | 274 lbs. (124 kg) | 324 lbs. (147 kg) |
| Burnishing System | | |
| Pad Diameter | (1) 20" (51 cm) | (1) 27" (69 cm) |
| Pad Motor Power (std): | (1) 3.0 hp (2,237 watts) | (1) 3.5 hp (2,610 watts) |
| Pad Motor Power (opt.): | NA | NA |
| Pad Speed: | 2000 rpm | 1900 rpm |
| Pad Engagement: | Direct | Direct |
| Variable Pad Pressure: | 10-65 lbs. (4.5-29 kg) | 10-65 lbs. (4.5-29 kg) |
| Pad Driver | Flexible | Flexible |
| BATTERY SYSTEM | | |
| Batteries (pad assist standard): | (3) 12-v / 160 ah | (3) 12-v / 175 ah |
| Batteries (pad assist option #1): | (3) 12-v / 175 ah | (3) 12-v / 225 ah |
| Batteries (pad assist option #2): | (6) 6-v / 245 ah | |
| Batteries (traction drive standard): | (3) 12-v / 175 ah | (3) 12-v / 175 ah |
| Batteries (traction drive option#1): | (3) 12-v / 225 ah | (3) 12-v / 225 ah |
| Batteries (traction drive option#2): | (6) 6-v / 245 ah | |
| Battery Run Time: | Up to 3 hours | Up to 3 hours |
| Charger (110-v / 60 Hz/auto): | 36-v / 25 amp | 36-v / 25 amp |
| Filtering System | | |
| Vacuum Description: | Passive | Passive |
| Filtering Material: | Disposable Bag | Disposable Bag |
| Screen Material: | 1 Micron | 1 Micron |
| Vacuum Power (opt.): | NA | NA |
| Drive System | | |
| Transport Power (unless pad assist model): | 0.5 hp (373 watts)(200-T) | 0.5 hp (373 watts)(200-T) |
| Forward Speed Control: | 0-4.5 mph (0-7 kph) | 0-4.5 mph (0-7 kph) |
| Reverse Speed Control: | 0-3 mph (0-5 kph) | 0-3 mph (0-5 kph) |
| Braking System: | Dynamic | Dynamic |
| Productivity | | |
| Cleaning Rate/Hour (Max.): | 35,248 sq. ft./hr. (10,744 sq. m/hr.) | 42,248 sq. ft./hr. (12,877 sq. m/hr.) |
| Cleaning Rate/Hour (Norm.): | 24,421 sq. ft./hr. (7,444 sq. m/hr.) | 29,421 sq. ft./hr. (8,968 sq. m/hr.) |
| GENERAL: | | |
| Sound Level (@driver's position) | 68 dBA | 68 dBA |
| Minimum Aisle for U-Turn: | 46" (117 cm) | 54" (137 cm) |
| Grade ability: | 7 degrees | 7 degrees |

RPS CORPORATION

P.O. Box 368
Racine, WI 53401
Phone: (800)634-4060

© RPS Corporation 2015.
All Rights Reserved.

Since our policy is one of constant improvement,
all specifications are subject to change without notice.

Authorized Distributor